



# شركة سمارت للدهانات SMART PAINT COMPANY

## SUPER PUTY

### Product Description:

High-quality water-based paste, which is based on a special formula.  
Designed to level surfaces

### The use:

It is used for interior applications on concrete, cement, and gypsum surfaces, and after sanding it gives a smooth surface.

### Properties:

Excellent filling for pores, superior smoothness after sanding.  
Ease of application.  
Excellent adhesion strength.



### Physical properties:

general look	matte
Color	white
Specific weight	1.70 ± 0.05 ASTM D1475
Solid size	50 ± 2% ASTM D2697
Dry layer thickening	100 microns
Theoretical spread rate	3 m <sup>2</sup> / l





# شركة سمارت للدهانات SMART PAINT COMPANY



## Drying time:

Surface dry 24 hours	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

### Surface Preparation:

The surface must be cohesive and free from holes, pits, bumps and any fragile areas. All excess areas must be removed and make sure that the surface is clean, dry and free of dirt, dust, grease, oils, salts and mold.

### Instructions for use:

The paint should be stirred well before use.

Sufficient amount of thinner may be added to obtain the appropriate viscosity for the application.

Do not paint over wet surfaces until after they are completely dry.

Not to paint the next layer unless the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and dehydration.

**Application tools:** brush and spray.

### Diluent:

Diluent: water.

Dilution ratio: No dilution is required.

### Storage conditions:

As it is

Shelf life: one year from the date of production.

